RFID system ID 15

Addressing device DPS/AS-i and AS-i accessories



Addressing device AS-i

Application:

The sturdy and handy addressing and diagnosis tool for initial operation, maintenance and service of AS-i systems provides the following:

Functions:

- Reads out slave addresses 0 to 31,
 A, B without scrolling with a clear and complete LCD display
- Reads out slave IO and ID codes (including extended ID codes 1 and 2)

- Standard addressing mode, and extended addressing mode from AS-i version 2.1.
- Programming of ID code1
 Slave function test, also for analog slaves with profile 7.1 to 7.4
- Recognition of all system components
 Memory, diagnosis and PC gateway functions
- Data transmission, data management and documentation of system parameters with optional software
- Connection via M12 plug (A-coded)
- Infrared interface



Scope of delivery: AS-i- addressing and testing appliance DPS/AS-i with batteries (4 x 1.5 V Mignon (AA) LR6).

DPS/AS-i addressing device

	No.
DPS/AS-i	3 842 406 173

AS-i accessories

AS-i branch terminal

to connect M12 plugs to an AS-i signal cable

AS-i branch terminal		No.
	_	3 842 406 176
	¥	

Connection cables

	M12	M12	I (m)	No.
M12 plug straight, M12 socket straight			0.5	3 842 406 193
			1.0	3 842 406 194
M12 plug straight, M12 socket angled	M12 M12	M12		No.
			0.5	3 842 406 166
			1.0	3 842 406 171