



Table top



- ▶ Table top for use in constructing Economic and Basic type Rexroth workstations for various mechanical loads
- ▶ Can be configured with variable dimensions or with fixed standard dimensions
- ▶ The Economic table top is suited for normal levels of mechanical stress on the table top surface
- ▶ The Basic table top with hard laminate coating is suited for high levels of mechanical stress on the table top surface
 - High abrasion resistance
 - High impact resistance and scratch resistance
 - Resistant to organic solvents, weak acidic and caustic materials, gasoline and oil
 - Briefly resistant to temperatures up to 180 °C
- ▶ Available in ESD-conductive version. Safe conduction (without extra wiring) of charges through volume conductive base material $R_{gp}/R_{pp} = 10^4 \dots 10^9 \Omega$ (DIN EN 61340-5-1)

Table top		3 842 998 250
Type	Design	Economic, Economic ESD, Basic, Basic ESD
B_{TP}	Table top width	400 ... 2700 mm
T_{TP}	Table top depth	300 ... 2000 mm

Material of Economic table top: Coated chipboard, 0.1 mm layer thickness; edging: ABS

Material of Basic table top: Coated chipboard, 0.8 mm layer thickness; edging: ABS

Scope of delivery: incl. fastening material

	B_{TP} (mm)	T_{TP} (mm)	ESD	No.
Table top Economic	1000	555		3 842 535 470
	1200	555		3 842 535 471
	1400	555		3 842 535 472
	1000	705		3 842 535 473
	1200	705		3 842 535 474
	1400	705		3 842 535 475
Table top Economic ESD	1000	555	Ⓐ	3 842 535 476
	1200	555	Ⓐ	3 842 535 477
	1400	555	Ⓐ	3 842 535 478
	1000	705	Ⓐ	3 842 535 479
	1200	705	Ⓐ	3 842 535 480
	1400	705	Ⓐ	3 842 535 481
Table top Basic	1000	555		3 842 535 489
	1200	555		3 842 535 490
	1400	555		3 842 535 491
Table top Basic ESD	1000	555	Ⓐ	3 842 535 482
	1200	555	Ⓐ	3 842 535 483
	1400	555	Ⓐ	3 842 535 484