





Basic hand switch (B)

- Push button for manual lifting and lowering
- With emergency stop
- Can be replaced with Comfort hand switch (**D**)
- Not suitable for oily environments, solution on request

	No.
B Basic hand switch	3 842 546 998




Holder for hand switch (C)

- To stow Basic and Comfort hand switches

Scope of delivery: includes fastening material for 10 mm slot


	No.
C Holder for hand switch	3 842 548 038



Comfort hand switch (D)

- For selection of “Manual” or “Automatic” mode
- Push button for manual lifting and lowering in “Manual” mode
- With emergency stop
- Not suitable for oily environments, solution on request

	No.
D Comfort hand switch	3 842 546 999




Comfort sensor unit (E)

- Works with the Comfort hand switch to control lifting and lowering in automatic mode

Scope of delivery: includes fastening material for 10 mm slot

	ESD	No.
E Comfort sensor unit		3 842 547 200



Mains cable (F)

- Ready-to-use; for simple, secure plug-and-play installation

	Country	L (m)	No.
F HD mains cable	D/F	5	3 842 554 183
	GB	5	3 842 555 603
	CH	5	3 842 555 605
	Open-ended	5	3 842 555 607
Mains cable	USA/CDN ¹	5	3 842 537 323

¹ UL and CSA test marks